

DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) Nr. 305/2011
(Construction Products Regulation)

Heatshield C100 / B50 Coated Batt System

Number of this Declaration of Performance: GHDoP04/A

Issue No: 01

Rev No: 01

- Unique Identification Code of Product Type:** Heatshield C100
- Intended Use / Uses:** Fire Stopping and Fire Sealing (Component of B50 System)
- Manufacturer:** Triton Middle East LLC, PO Box 3350, New Industrial Area, Umm Al Quwain, U.A.E.
- Authorised Representative:** 24HOUR SOLUTIONS B.V. (T/a : 24HOUR-AR), Van Nelleweg 1,304 BC, Rotterdam, Netherlands
- System/s of AVCP:** AVCP - System 1
- European Assessment Document:** EAD 350454-00-1104 - September 2017
European Technical Assessment: ETA 23/0901
Technical Assessment Body: UL International (Netherlands) B.V.
Notified Body: 2821
- Declared Performance:**

Essential Characteristics	Performance / Harmonised Technical Specification
Mechanical Resistance & Stability	Not Relevant
Reaction to Fire (EN 13501-1)	Class E according to EN13051-1
Resistance to Fire (EN 13501-2)	Resistance to fire performance & field of application in accordance with EN13501-2 See ETA 23/0901 clause - Annex A
Air Permeability (EN 1026:2000)	NPD
Water Permeability (EAD 350141-00-1106 -3 Annex C)	NPD
Dangerous Substances	See ETA 23/0901 Clause 1.8 – Declaration of the Manufacturer
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion	NPD
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
Durability and Serviceability (EOTA TR 024:2019)	Type: Z1 - Intended for use in conditions specified in EOTA TR024:2019

Link to online copy of the Declaration of Performance: www.greentech-heatshield.com

Signed for and on behalf of the manufacturer by:

G Metcalfe

.....
Gary Metcalfe – Director

Date: 05 December 2025